

Dream Machine Cover Supply List Required Before Class

- Basic sewing supplies:
- Sharp Fabric Scissors, blade at least 9" long or a rotary mat and cutter
- Straight Pins at least 1 ¼" long with a colored head (not craft pins)
- Tap Measure 60" long, plastic, not cloth
- Metal seam guide 5-6" long
- Seam Ripper
- Standard, piping, edge stitch and zipper feet for your sewing machine
- Hand sewing needle
- Rotary Cutter; mat, and ruler
- Erasable Fabric Marker or chalk marker
- Needles 80/12 or 90/14
- Sewing Machine
- Pattern provided by the instructor

- Brother Dream Machine Cover Supplies
- 1.25 yards of Main fabric (recommend quilting cotton fabric)
- 1.25 yards of Lining fabric (recommend quilting cotton fabric)
- 1 ½ yards of batting
- 1.25 fusible fleece
- Binding fabric: 3 yards of coordinating bias binding 2 ½" wide
- 2 – 1" buttons
- 2 elastic hair bands or comparable elastic pieces
- 21" of 3/8" to ½" grosgrain ribbon coordinating color
- Ribbon trim at bottom (optional) 3 yards of 1" wide grosgrain ribbon, 3 yards of 3/8 or ½" satin ribbon, coordinating embroidery thread, 3 yards of medium tear away stabilizer 7/8" wide
- 2 ¼ yards of purchased bias piping for side panels (optional)
- Thread to match fabric main and lining fabric; if adding ribbon trim add matching threads

- Pre-Work, required before class
- Main fabric cut one piece 43" (from width of fabric) X 36" high *NOTE: if*

fabric is directional you may want to make a seam in the middle so both pieces are pointed in the same direction.

- Lining cut one piece 41 $\frac{3}{4}$ " (from width of fabric) X 34 $\frac{1}{2}$ " high
- Side Panels cut 2 pieces 13" wide X 16" high
- Fusible fleece cut same as Main fabric
- Batting cut one piece same as Main fabric and 2 pieces same as Side Panels
- Quilt Main fabric layering fabric, fusible fleece and batting, with batting on the bottom and the main fabric on top, sandwiching the fusible in the middle.
- Quilt both Side Panels using batting only (no fusible fleece needed)
- Quilt using vertical straight lines about 2" apart
- Once quilting has been completed on the 3 pieces trim and true to the following finish size; Main fabric 41 $\frac{3}{4}$ " (from width of fabric) X 34 $\frac{1}{2}$ ", Side Panels 11 $\frac{1}{2}$ " wide X 14 $\frac{1}{2}$ " high
- Cut bias binding 2 $\frac{1}{2}$ " wide and 3 yards long; if making your own optional piping please make before class
- Optional Ribbon trim; fuse tear away stabilizer to 1" grosgrain ribbon; place satin ribbon on top of grosgrain ribbon in the middle and sew a decorative stitch on top of the satin ribbon

NOTE: Sewing Machines:

For those students who have sewing machines they must bring along with their sewing machines the following:

- Before class you must know how to thread your sewing machine and the bobbin
- Must bring all the sewing machine attachments, feet, screw driver, etc.
- Must have owner's manual for your machine
- Bring 2 extra bobbins with no thread
- Remember to bring the power cord and foot pedal

For those students who need Sewing machines please contact store personnel for available sewing machine rentals. Machine rentals are \$35 per day, first come, first serve.