Tomorrow's Treasurers Ruler Case REVISED Supply List Required Before Class

- 1) Basic sewing supplies:
 - Sharp Fabric Scissors, at least 7-8" long
 - Straight Pins at least 1 ¼ " long with a colored head
 - Hand Sewing needles
 - Metal seam guide 5-6" long
 - Wonder Clips optional
 - Seam Ripper
 - Thread to match your fabrics
 - Standard foot, zipper foot, and edge foot for your sewing machine
 - 90/14 universal sewing machine needle
 - Sewing Machine
 - Decorative thread as an accent for top of pockets (optional)
 - Bring any leftover fabric to class
- 2) Supplies needed for class:
 - a. Rulers planned for the case
 - b. Zippers by the yard 1 package, prefer #5 coil (width including tape should be 1 ¼"), plus 2 large zipper pulls (1-1/8")
 - c. Webbing for handles 1" wide; top handles 30"; optional side handles 30"
 - d. Main case fabric is 2 pieces, 1 piece of batting or Soft & Stable interfacing,
 - e. Bias binding 3 yards; if making your own binding use 1 ½"wide; if using purchased binding use ½" double fold bias seam binding; if using binding to finish top of pockets increase your bias binding accordingly
 - f. 1 yard of fabric for pockets depending on the number of pockets and size; feel free to use fabric scraps for the pockets
- 3) Pre-Work Required,
 - a. Main fabric cut 2 pieces 21 wide X 30" high; cut the same of either batting or Soft & Stable; sandwich the batting or Soft & Stable between the 2 main fabric pieces and quilt with vertical lines 1-2" apart (Note when using directional fabric make sure both sides are going in the same direction); square this quilted rectangle to 20" X 29" (this size will accommodate rulers 8" wide and 24" high, If using a larger ruler increase size accordingly); slightly round the four corners; now serge all raw edges
 - b. Cut all pockets for the rulers you plan for the case; for the pocket measurement add 2"to the ruler width and subtract 2-3" from the ruler length; serge all sides of

the pockets (when binding the top of pocket sew your binding on first and then serge); sew a 3/8" guide seam on the 2 long sides and ½" on the top and bottom of all pockets (this will become your press line), when binding the top of pocket delete the guide seam; plan on 3-4 pockets for one side and 2-3 pockets for the second side; pockets will be stacked largest on the bottom and smallest on top

c. Cut 2 zipper tabs 1-3/4" wide X 4" long

NOTE: Sewing Machines:

You must bring along with your sewing machines the following:

- 1. Must bring the sewing machine attachments, feet (referenced above), screw driver, etc.
- 2. Must have owner's manual for your machine
- 3. Bring 2 extra bobbins with no thread
- 4. Remember to bring the power cord and foot pedal

For those students who need Sewing machines please contact store personnel for available sewing machine rentals.